

Technical Specification

Rated Voltage	220 Volt/ 50 Hz
Working Width	450 mm
Squeegee Width	755 mm
Brush	1 Nos
Brush Diameter	450 mm
Brush Pressure	30 Kg
Solution Tank	27 L
Recovery Tank	30 L
Size (L*W*H*)	1050*450*700 mm
Machine Weight	75 Kg
Noise Level	70 db
Brush RPM	150 RPM

Walk Behind Scrubber Drier **ASD 30E-1**



www.sicuro.in



Toll Free No: 1800 419 8875



neeraj@sicuro.in, mcsharma@sicuro.in



Available on

GeM
Government
e Marketplace

Sicuro Ventures Private Limited

Corporate Office: 106- Bharat Nagar, New Delhi-110052

Mob: +91-98370-62624, +91-98110-40704

Technical Specification

Rated Voltage	220 Volt/ 50 Hz
Working Width	450 mm
Squeegee Width	755 mm
Brush	1 Nos
Brush Diameter	450 mm
Brush Pressure	30 Kg
Solution Tank	27 L
Recovery Tank	30 L
Size (L*W*H*)	1050*450*700 mm
Machine Weight	75 Kg
Noise Level	70 db
Brush RPM	150 RPM

Walk Behind Scrubber Drier **ASD 30E-1**



www.sicuro.in



Toll Free No: 1800 419 8875



neeraj@sicuro.in, mcsharma@sicuro.in



Sicuro Ventures Private Limited

Corporate Office: 106- Bharat Nagar, New Delhi-110052

Mob: +91-98370-62624, +91-98110-40704

TECHNICAL SPECIFICATION

Number of Brushes	1
Brush width	NA
Brush Diameter(mm)	401-450
Rolling Brush Motor(w)	800
Brush Load (Kg)	22
Brush Speed (rpm)	280
Brush Type	Disc
Scrubbing Width(mm)	401-500
Suction Width (mm)	701-1400
Cleaning Productivity	1201-2000
Net Weight of machine (kg)	101-200
Water Suction Motor (w)	351-600
Forward Seep Max (km/h)	4
Vacuum Pressure (kpa)	52
Power cable length (mtr)	20
Wheels	Solid Rubber
Material of Chassis	Mild Steel as per IS:2062 (Grade-A)
Material of Body	Polypropylene
Fresh water tank (ltr)	40
Dirty water tank (ltr)	40
Noise Level (db(A))	73.5



Sicuro ASD 45E

Sicuro Ventures Private Limited

Corporate Office: 106- Bharat Nagar, New Delhi-110052

Mob: +91-98370-62624, +91-98110-40704

Email: neeraj@sicuro.in, mcsharma@sicuro.in

TECHNICAL SPECIFICATION

	Battery	Electronic
Voltage (V/hz)	100-240 / 50-60	220-240 / 50-60
Battery Charger	24VDC-10A	-
Total Power (W)	540	900
Cable (ft)	15 (50)	15 (50)
Vacuum Motor (W)	360	600
Water lift	1250 (49.2)	1800 (71)
Air Volume lt/sec (CFM)	35 (74)	40 (85)
Water Dosing	Pump	Pump
Brush Motor Rotafil (W)	150	300
Brush Roller	80/460(3.2/18.1)	80/460(3.2/18.1)
Brush Speed RPM	1200	1200
Suction Blade mm (inch)	520 (20.47)	520 (20.47)
Water Tank lt. (gal)	10 (2.95)	10 (2.95)
Recovery Tank lt. (gal)	13 (3.85)	13 (3.85)
Working Capacity sqm./h	1500 (16,000)	1300 (14,000)
Recharge Time (h)	3	-
Base Height mm (inch)	230 (9)	230 (9)
Noise Level db (A)	69	69
Total Weight kg (lb)	60,4 (133)	43 (95)
Sealing Protection	IPX 4	IPX 4



Sicuro ASD 350B

Sicuro Ventures Private Limited

Corporate Office: 106- Bharat Nagar, New Delhi-110052

Mob: +91-98370-62624, +91-98110-40704

Email: neeraj@sicuro.in, mcsharma@sicuro.in

Technical Specification

Brush	2 Nos
Brush Diameter	300 mm
Brush Motor	500 W
Brush Load	22 Kg
Brush Speed	190 Rpm
Machine Working Type	Ride on
Brush Type	Disc
Scrubbing Width	600 mm
Suction Width	650 mm
Cleaning Productivity	4000 m ² /h
Net Weight of Machine	180 Kg
Water Suction Motor	1200 W
Forward Speed Max	5.5
Vacuum Pressure	12 kpa
Fresh Water Tank	51-90
Dirty Water Tank	56-95
Noise Level	70 db(A)

Ride on Scrubber Drier **RS 510 B**



www.sicuro.in



Toll Free No: 1800 419 8875



neeraj@sicuro.in, mcsharma@sicuro.in



Available on

GeM
Government
e Marketplace

Sicuro Ventures Private Limited

Corporate Office: 106- Bharat Nagar, New Delhi-110052

Mob: +91-98370-62624, +91-98110-40704

TECHNICAL SPECIFICATION

Scrubbing Width(mm)	760 mm
Squeegee Width (mm)	1000 mm
Productivity	4500 m ² / Hour
Speed	0-7 Km/ Hour
Power	24 Volt
Brush Diameter/Nos	390 mm/ 2 Nos
Brush Speed	180 RPM
Brush Pressure	25-60 Kg
Fresh Water Tank	110 L
Recovery Water Tank	125 L
Battery	6 V*4 Nos (200 Ah)

Sicuro RS 760B



Sicuro Ventures Private Limited

Corporate Office: 106- Bharat Nagar, New Delhi-110052

Mob: +91-98370-62624, +91-98110-40704

Email: neeraj@sicuro.in, mcsharma@sicuro.in

RIDE ON SCRUBBER DRIER

SICURO™
Work Together

SICURO RS 540B



SICURO RS 660B



SICURO RS 860B



TECHNICAL SPECIFICATION

MODEL	RS 540B	RS 660B	RS 860B
Rated Voltage	DC 24V	DC 24V	DC 36V
Working width	540mm	660mm	860mm
Squeegee Width	800mm	1000mm	1150mm
Brush Quantity	1 Nos	2 Nos	2 Nos
Brush Diameter	540mm	340mm*2	430mm*2
Brush Pressure	30 kg	30-60 Kg	45-75 Kg
Forward Speed	0-5 Km/Hr	0-6 Km/Hr	0-7 Km/Hr
Max Gradient	8%	10%	10%
Solution Tank Capacity	65L	110L	180L
Recovery Tank Capacity	70L	125L	200L
Dimension in MM (L*W*H)	1300*720*1340	1560*840*1450	1750*940*1450
Machine Weight	180 kg	420 Kg	600 Kg
Noise Level	<68db (A)	<68db (A)	<68db (A)



- The working width of 860 mm provides extended fields of applications and greater area coverage in the 180-200 liter class.
- The Ride on scrubber driver for use in small, Medium and Large areas. Through cleaning up to have edge consistently high pressure in combination with a swivel squeegee.

* Specifications can be changed without prior notice due to regular up gradations of the product.